



PROUDLY AUSTRALIAN OWNED
DESIGNED & ASSEMBLED IN MELBOURNE



PREMIUM GERMAN MADE
MOTOR SYSTEMS

Product Detail



Model Number	X7P04B (Black Finish) / X7P04W (White Finish)
Hood Mounting	Island Mounted Canopy
Cooking Coverage	Suits 30cm - 60cm Cooking Surfaces
Filtration	S-Flow Baffle Filters 1x (H-25) - Dishwasher Safe
Lighting	LED 2x (Warm White 1.0W)
Finish	AISI304 1.0mm Food Grade Stainless Steel with Satin Black or Satin White Finish
Controls	LED Backlit 4 Button <i>mastermind</i> Electronic Control with LED Speed Indicator
Speed Settings	3 Speed + Boost Mode
Timer Function	Programmable Timer (10min Increments) Auto fan shut off after 2-hours of inactivity
Outlet	Top Duct Outlet
Ducting (Remote)	Dia. 200mm Acoustic Flexi Ducting - Five (5) Meter Length (Supplied)
Ducting (On Board)	Optional On Board Motor Ducting Kits Available Power Motor - Dia. 150mm (Recommended)
Hood Width	360mm
Hood Depth	360mm
Hood Height (Fascia)	800mm (standard) - Custom Height Available - 400mm (min)
Installation Height	700 - 750mm* (Recommended) 600mm* (Minimum)

* Clearance above the highest point of the cooktop to the underside of hood



Filtration Zone

Dimensioned Drawing



Whispair Endurance Warranty



Your Hood. Your Colour. Your Way.

Available Finishes



Available Models - Select Your Motor Solution & Optional Finish

Satin Black Finish

On Board

X7P04B5.OP (T)	Power 1,020m ³ /hr (Top Ducted)	SPL: 53.9dB(A)
----------------	--	----------------

Remote External (Roof or Wall Mounted)

X7P04B5.EL	Lite 800m ³ /hr	SPL: 43.8dB(A) In / 52.7dB(A) Out
X7P04B5.EP	Pro 1,140m ³ /hr	SPL: 52.6dB(A) In / 58.5dB(A) Out

Remote Inline (Through Wall or Eave)

X7P04B5.IL	Lite 800m ³ /hr	SPL: 39.3dB(A) In / 52.7dB(A) Out
X7P04B5.IP	Pro 1,140m ³ /hr	SPL: 49.6dB(A) In / 58.5dB(A) Out

Satin White Finish

On Board

X7P04W5.OP (T)	Power 1,020m ³ /hr (Top Ducted)	SPL: 53.9dB(A)
----------------	--	----------------

Remote External (Roof or Wall Mounted)

X7P04W5.EL	Lite 800m ³ /hr	SPL: 39.3dB(A) In / 52.7dB(A) Out
X7P04W5.EP	Pro 1,140m ³ /hr	SPL: 49.6dB(A) In / 58.5dB(A) Out

Remote Inline (Through Wall or Eave)

X7P04W5.IL	Lite 800m ³ /hr	SPL: 39.3dB(A) In / 52.7dB(A) Out
X7P04W5.IP	Pro 1,140m ³ /hr	SPL: 49.6dB(A) In / 58.5dB(A) Out

*Your Hood. Your Colour. Your Way. (Optional Island Mounted Canopy Finish)**

X1P7.CUS	Paint Finish - Custom Colour
X1FP.010*	Height Extension - Plus 100mm

*Additional charges apply

SPL - Nominal Sound Pressure Level on Boost (Max) Speed